



***** repair part ***** SIMATIC S7-400, function module FM 450-1 for counter function with 2 channels incl. configuration package on CD

Supply voltage	
Auxiliary voltage 1L+, load voltage 2L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V; Dynamic 18.5 V
• permissible range, upper limit (DC)	28.8 V; dynamic 30.2 V
Input current	
from load voltage 1L+ (without load), max.	40 mA
from backplane bus 5 V DC, max.	450 mA
Encoder supply	
5 V encoder supply	
• 5 V	Yes; 5.2 V $\pm 2\%$
• Short-circuit protection	Yes
• Output current, max.	300 mA
24 V encoder supply	
• 24 V	Yes; 1L+ (-3 V)
• Short-circuit protection	Yes
• Output current, max.	300 mA
Power loss	
Power loss, typ.	9 W
Digital inputs	
Number of digital inputs	6
Functions	1 for gate start, 1 for gate stop, 1 for setting the counter
Input voltage	
• for signal "0"	-28.8 ... +5V
• for signal "1"	+11 to +28.8V
Input current	
• for signal "1", typ.	9 mA
Input delay (for rated value of input voltage)	
• Input frequency (with a time delay of 0.1 ms), max.	200 kHz
for standard inputs	
— parameterizable	Yes
— at "0" to "1", max.	2.5 μ s; $\geq 2.5 \mu$ s (200 kHz); $\leq 25 \mu$ s (20 kHz)
Digital outputs	
Number of digital outputs	4
Short-circuit protection	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	2L+ (-39 V)
Output voltage	
• for signal "0", max.	3 V
• for signal "1", min.	2L+ (-1,5 V)
Output current	

• for signal "1" rated value • for signal "1" permissible range for 0 to 60 °C, min. • for signal "1" permissible range for 0 to 60 °C, max.	0.5 A 5 mA 0.6 A		
Output delay with resistive load			
• "0" to "1", max.	300 µs		
Encoder			
Connectable encoders			
• Incremental encoder (symmetrical) • Incremental encoder (asymmetrical) • 24 V initiator • 24 V directional element	Yes; With 2 pulse trains offset by 90° Yes Yes Yes; 1 pulse train, 1 direction level		
Interrupts/diagnostics/status information			
Status indicator	Yes; 14 green LEDs for status of CR, DIR, inputs and outputs		
Diagnostics function	Yes		
Alarms			
• Diagnostic alarm • Hardware interrupt	Yes; Parameterizable Yes; Parameterizable		
Diagnoses			
• Diagnostic information readable	Yes		
Diagnostics indication LED			
• internal fault INTF (red) • external fault EXTf (red) • Status indicator digital input (green) • Status indicator digital output (green)	Yes Yes Yes Yes		
Counter			
Number of counter inputs	2; 32 bit or ±31 bit		
Counter input 5 V			
• Type • Terminating resistor • Differential input voltage • Counting frequency, max.	RS 422 220 Ω min. 0.5 V 500 kHz		
Counter input 24 V			
• Input voltage for signal "0" • Input voltage for signal "1" • Input current for signal "1", typ. • Counting frequency, max.	-30 to +5 V +11 to +30V 9 mA 200 kHz		
Potential separation			
Potential separation digital inputs			
• between the channels and backplane bus	Yes; Optocoupler		
Potential separation digital outputs			
• between the channels and backplane bus	Yes; Optocoupler		
Potential separation counter			
• between the channels and backplane bus	Yes; Optocoupler		
Isolation			
Isolation tested with	500 V		
connection method			
required front connector	1x 48-pin		
Dimensions			
Width	25 mm		
Height	290 mm		
Depth	210 mm		
Weights			
Weight, approx.	650 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-05
	eClass	12	27-24-22-05
	eClass	9.1	27-24-22-05
	eClass	9	27-24-22-05

eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates		
General Product Approval	EMV	For use in hazardous locations



[KC](#)



For use in hazardous locations



[FM](#)



[Type Examination Certificate](#)



Marine / Shipping



[CCS \(China Classification Society\)](#)

last modified: 5/22/2024