



SIMATIC S7-400, interface module Send IM 460-3 for distributed coupling up to 102 m, with C-bus

Figure similar

Input current	
from backplane bus 5 V DC, max.	1 550 mA
Power loss	
Power loss, max.	7 750 mW
Hardware configuration	
Cable length between first and last interface module, max.	102.25 m
connection method	
termination plug	6ES7461-3AA0-7AA0
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	630 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



EG-Konf.

[Miscellaneous](#)





UL

[KC](#)



RCM

EMV

For use in hazardous locations



[FM](#)



For use in hazardous locations

Marine / Shipping



[Type Examination Certificate](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

3/12/2024 