

MLFB-Ordering data

6SE6440-2UC21-5BA1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data                              |                          | General tech. specifications             |               |
|-----------------------------------------|--------------------------|------------------------------------------|---------------|
| <b>Input</b>                            |                          | <b>Power factor <math>\lambda</math></b> | 0.95          |
| <b>Number of phases</b>                 | 1 / 3 AC                 | <b>Efficiency <math>\eta</math></b>      | 0.96          |
| <b>Line voltage</b>                     | 200 ... 240 V $\pm 10$ % | <b>Ambient conditions</b>                |               |
| <b>Line frequency</b>                   | 47 ... 63 Hz             | <b>Cooling</b>                           | Fan           |
| <b>Rated current (HO)</b>               | 14.40 A / 8.30 A         | <b>Ambient temperature</b>               |               |
| <b>Output</b>                           |                          | <b>Operation (HO)</b>                    | -10 ... 50 °C |
| <b>Number of phases</b>                 | 3 AC                     | <b>Transport</b>                         | -40 ... 70 °C |
| <b>Rated voltage</b>                    | 240 V                    | <b>Storage</b>                           | -40 ... 70 °C |
| <b>Rated power (HO)</b>                 | 1.50 kW / 2.00 hp        |                                          |               |
| <b>Rated current (HO)</b>               | 7.40 A                   |                                          |               |
| <b>Pulse frequency</b>                  | 16000 Hz                 |                                          |               |
| <b>Output frequency for V/f control</b> | 0 ... 650 Hz             |                                          |               |

As a result of legal stipulations, a limit to 550 Hz is in production

### Overload capability

#### High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

MLFB-Ordering data

6SE6440-2UC21-5BA1



Figure similar

### Mechanical data

Degree of protection IP20 / UL open type

Size FSB

Net weight 3.30 kg

Width 149.0 mm

Height 202.0 mm

Depth 172.0 mm

### Inputs / outputs

#### Standard digital inputs

Number 6

#### Relay output

Number 3

#### Analog inputs

Number 2

#### Analog outputs

Number 2

#### PTC/ KTY interface

Number 1

### Connections

#### Motor end

Conductor cross-section 6.00 mm<sup>2</sup>