SIEMENS

Data sheet 6ES7417-5HT06-0AB0



SIMATIC S7-400H, CPU 417-5H, central processing unit for S7-400H and S7-400F/FH, 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for sync modules, 32 MB memory (16 MB data/16 MB program)

General information	
Product type designation	CPU 417-5H PN/DP
HW functional status	1
Firmware version	V6.0
Product function	
● Isochronous mode	No
Engineering with	
● Programming package	As of STEP 7 V5.5 SP2 with HF1
CiR - Configuration in RUN	
CiR synchronization time, basic load	60 ms
CiR synchronization time, time per I/O byte	0 µs
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1.6 A
from backplane bus 5 V DC, max.	1.9 A
from backplane bus 24 V DC, max.	150 mA; 150 mA per DP interface
from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	7.5 W
Memory	
Type of memory	RAM
Work memory	
● integrated	32 Mbyte
● integrated (for program)	16 Mbyte
● integrated (for data)	16 Mbyte
● expandable	No
Load memory	
● expandable FEPROM	Yes; with Memory Card (FLASH)
● expandable FEPROM, max.	64 Mbyte
● integrated RAM, max.	1 Mbyte
● expandable RAM	Yes
● expandable RAM, max.	64 Mbyte
Backup	
● present	Yes
● with battery	Yes; all data
● without battery	No
Battery	
Backup battery	
● Backup current, typ.	180 µA; Valid up to 40°C

Subject to change without notice
© Copyright Siemens

● Backup current, max.	1 000 µA
● Backup time, max.	Dealt with in the module data manual with the secondary conditions and the factors of influence
● Feeding of external backup voltage to CPU	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	7.5 ns
for word operations, typ.	7.5 ns
for fixed point arithmetic, typ.	7.5 ns
for floating point arithmetic, typ.	15 ns
CPU-blocks	
DB	
● Number, max.	16 000; Number range: 1 to 16000
● Size, max.	64 kbyte
FB	
● Number, max.	8 000; Number range: 0 to 7999
● Size, max.	64 kbyte
FC	
● Number, max.	8 000; Number range: 0 to 7999
● Size, max.	64 kbyte
OB	
● Number, max.	see instruction list
● Size, max.	64 kbyte
● Number of free cycle OBs	1; OB 1
● Number of time alarm OBs	8; OB 10-17
● Number of delay alarm OBs	4; OB 20-23
● Number of cyclic interrupt OBs	9; OB 30-38
● Number of process alarm OBs	8; OB 40-47
● Number of DPV1 alarm OBs	3; OB 55-57
● Number of startup OBs	2; OB 100, 102
● Number of asynchronous error OBs	9; OB 80-88
● Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
● per priority class	24
● additional within an error OB	2
Counters, timers and their retentivity	
S7 counter	
● Number	2 048
Retentivity	
— adjustable	Yes
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
● present	Yes
● Type	SFB
● Number	Unlimited (limited only by RAM capacity)
S7 times	
● Number	2 048
Retentivity	
— adjustable	Yes
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
● present	Yes
● Type	SFB
● Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	Total working and load memory (with backup battery)

Subject to change without notice
© Copyright Siemens

Flag	
● Size, max.	16 384 byte
● Retentivity available	Yes
● Retentivity preset	MB 0 to MB 15
● Number of clock memories	8; in 1 memory byte
Local data	
● adjustable, max.	64 kbyte
● preset	32 kbyte
Address area	
I/O address area	
● Inputs	16 kbyte
● Outputs	16 kbyte
Process image	
● Inputs, adjustable	16 kbyte
● Outputs, adjustable	16 kbyte
● Inputs, default	1 024 byte
● Outputs, default	1 024 byte
● consistent data, max.	244 byte
● Access to consistent data in process image	Yes
Subprocess images	
● Number of subprocess images, max.	15
Digital channels	
● Inputs	131 072
— of which central	131 072
● Outputs	131 072
— of which central	131 072
Analog channels	
● Inputs	8 192
— of which central	8 192
● Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	119
Multicomputing	No
Interface modules	
● Number of connectable IMs (total), max.	6
● Number of connectable IM 460s, max.	6
● Number of connectable IM 463s, max.	4; Single mode only
Number of DP masters	
● integrated	2
● via CP	10; CP 443-5 Extended
● Mixed mode IM + CP permitted	No
● via interface module	0
Number of IO Controllers	
● integrated	1
● via CP	0
Number of operable FMs and CPs (recommended)	
● FM	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
● CP, PtP	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
● PROFIBUS and Ethernet CPs	14; Of which max. 10 CP as DP master
Slots	
● required slots	2
Time of day	
Clock	
● Hardware clock (real-time)	Yes
● retentive and synchronizable	Yes
● Resolution	1 ms
● Deviation per day (buffered), max.	1.7 s; Power off

Subject to change without notice
© Copyright Siemens

● Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
● Number	16
● Number/Number range	0 to 15
● Range of values	SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2^31 - 1 hours
● Granularity	1 h
● retentive	Yes
Clock synchronization	
● supported	Yes
● to MPI, master	Yes
● on MPI, device	Yes
● to DP, master	Yes
● on DP, device	Yes
● in AS, master	Yes
● in AS, device	Yes
● on Ethernet via NTP	Yes; As client
Time difference in system when synchronizing via	
● Ethernet, max.	10 ms; Via NTP
● MPI, max.	200 ms
Interfaces	
Number of RS 485 interfaces	2
Number of other interfaces	2; Fiber-optic interface
Optical interface	No
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
● RS 485	Yes
● Output current of the interface, max.	150 mA
Protocols	
● MPI	Yes
● PROFIBUS DP master	Yes
● PROFIBUS DP device	No
MPI	
● Number of connections	44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
● Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
● Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
● Transmission rate, max.	12 Mbit/s
● max. number of DP devices	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No

© Copyright Siemens

— activation/deactivation of DP devices	No
— Direct data exchange (slave-to-slave communication)	No
— DPV1	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP device	
— user data per DP device, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
1st interface / PROFIBUS DP device / header	
● Number of connections	No configuration of CPU as DP slave
2. Interface	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes; Autosensing
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	No
Interface types	
● RJ 45 (Ethernet)	Yes
● Number of ports	2
● integrated switch	Yes
Protocols	
● PROFINET IO Controller	Yes
● PROFINET IO Device	No
● PROFINET CBA	No
● PROFIBUS DP master	No
● PROFIBUS DP device	No
● Open IE communication	Yes
● Web server	No
● Point-to-point connection	No
● Media redundancy	Yes
PROFINET IO Controller	
● Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— S7 communication	Yes
— Isochronous mode	No
— Shared device	Yes; Single mode only
— Prioritized startup	No
— Number of connectable IO Devices, max.	256; In redundant mode via both interfaces
— Number of connectable IO Devices for RT, max.	256
— of which in line, max.	256
— Activation/deactivation of IO Devices	No
— IO Devices changing during operation (partner ports), supported	No
— Device replacement without swap medium	Yes
— Send cycles	250 µs, 500 µs, 1 ms, 2 ms, 4 ms
— Updating time	250 µs to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
— User data consistency, max.	1 024 byte
Open IE communication	
● Number of connections, max.	118
● Local port numbers used at the system end	0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535

Subject to change without notice
© Copyright Siemens

● Keep-alive function, supported	Yes
3. Interface	
Interface type	PROFIBUS DP
Interface types	
● RS 485	Yes
● Output current of the interface, max.	150 mA
Protocols	
● PROFIBUS DP master	Yes
● PROFIBUS DP device	No
PROFIBUS DP master	
● Number of connections, max.	32
● Transmission rate, max.	12 Mbit/s
● max. number of DP devices	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No
— activation/deactivation of DP devices	No
— Direct data exchange (slave-to-slave communication)	No
— DPV0	Yes
— DPV1	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP device	
— user data per DP device, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
4. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
5. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
Protocols	
Redundancy mode	
Media redundancy	
— Switchover time on line break, typ.	200 ms
— Number of stations in the ring, max.	50
SIMATIC communication	
● S7 routing	Yes
Open IE communication	
● TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	118
— Data length, max.	32 kbyte
— several passive connections per port, supported	Yes
● ISO-on-TCP (RFC1006)	Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs
— Number of connections, max.	118
— Data length, max.	32 kbyte; 1 452 bytes via CP 443-1 Adv.
● UDP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	118

Subject to change without notice
© Copyright Siemens

— Data length, max.	1 472 byte
Web server	
● supported	No
Isochronous mode	
Equidistance	No
communication functions / header	
PG/OP communication	Yes
● Number of connectable OPs with message processing	119; When using Alarm_S/SQ and Alarm_D/DQ
● Number of connectable OPs without message processing	119
Data record routing	Yes
Global data communication	
● supported	No
S7 basic communication	
● supported	No
S7 communication	
● supported	Yes
● as server	Yes
● as client	Yes
● User data per job, max.	64 kbyte
● User data per job (of which consistent), max.	462 byte; 1 variable
S5 compatible communication	
● supported	Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)
● User data per job, max.	8 kbyte
● User data per job (of which consistent), max.	240 byte
● Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.	64/64
Standard communication (FMS)	
● supported	Yes; Via CP and loadable FB
Number of connections	
● overall	120
● usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
● usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
● usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
● usable for S7 communication	
— reserved for S7 communication	0
— adjustable for S7 communication, max.	0
● usable for routing	
— reserved for routing	0
— adjustable for routing, max.	0
S7 message functions	
Number of login stations for message functions, max.	119; max. 119 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 16 with Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC)
Symbol-related messages	No
SCAN procedure	No
Program alarms	Yes
Process diagnostic messages	Yes
simultaneously active Alarm_S blocks, max.	1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks
Alarm 8-blocks	Yes
● Number of instances for alarm 8 and S7 communication blocks, max.	10 000
● preset, max.	1 200
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	64
Test commissioning functions	
Status block	Yes

Subject to change without notice
© Copyright Siemens

Single step	Yes
Number of breakpoints	16
Status/control	
● Status/control variable	Yes; Up to 16 variable tables
● Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
● Number of variables, max.	70
Forcing	
● Forcing	Yes
● Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
● Number of variables, max.	512
Diagnostic buffer	
● present	Yes
● Number of entries, max.	3 200
— adjustable	Yes
— preset	120
Service data	
● can be read out	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	Yes
● Limit class B, for use in residential areas	No
configuration / header	
Configuration software	
● STEP 7	Yes
configuration / programming / header	
● Command set	see instruction list
● Nesting levels	7
● Access to consistent data in process image	Yes
● System functions (SFC)	see instruction list
● System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
configuration / programming / number of simultaneously active SFC / header	
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	8
— DP_TOPOL	1
configuration / programming / number of simultaneously active SFB / header	
— RDREC	8
— WRREC	8
Know-how protection	
● User program protection/password protection	Yes
● Block encryption	Yes; With S7 block Privacy
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	995 g
Classifications	

Subject to change without notice
© Copyright Siemens

	Version	Classification
eClass	14	27-24-22-07
eClass	12	27-24-22-07
eClass	9.1	27-24-22-07
eClass	9	27-24-22-07
eClass	8	27-24-22-07
eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236
IDEA	4	3565
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



Miscellaneous





KC

Miscellaneous

General Product Approval | For use in hazardous locations







FM





For use in hazardous locations | Functional Saftey | Maritime application

Type Examination Certificate





Type Examination Certificate





Maritime application | Environment





NK / Nippon Kaiji Kyokai



CCS (China Classification Society)



Industrial Communication

PROFIsafe

last modified: 6/7/2025

Subject to change without notice
© Copyright Siemens